


Designed with a galvanized steel drywall bead tapping flange.




FRONT ELEVATION

STANDARD CONSTRUCTION:

- MATERIAL** - SATIN FINISH GALVANIZED (GALVANNEALED) STEEL.
- PANEL** - 1.31mm [18 ga.], SELF CLOSING.
- LINER** - 0.85mm [22ga.]
- FRAME** - 1.61mm [16 ga.]
- FLANGE** - GALVANIZED STEEL DRYWALL BEAD TAPING FLANGE
- HINGE** - CONTINUOUS ROD HINGE.
- LATCH** - ¼" ALLEN KEY, WITH INTERIOR RELEASE.
- INSULATION** - 38mm [1½"] HIGH TEMPERATURE
- FINISH** - RUST INHIBITIVE PRIME COAT (OFF-WHITE).

* Specifications subject to change without notice.



SECTION A-A


PROJECT: _____

CONTRACTOR: _____

ARCH. OR ENG.: _____

DATE: _____

These drawings are the property of Maxam Metal Products Ltd. and incorporates information which is proprietary. Publication and/or public distribution in whole or in part is expressly prohibited without the prior written consent of Maxam Metal Products Ltd. The information herein remains the property of Maxam Metal Products Ltd. All rights reserved.

DWN BY KB	DATE Feb. / 2014	DWG. NO. Sheet 1 of 2	REV. 
--------------	---------------------	--------------------------	-----------------------------------------------------------------------------------------------

INSTALLATION:

The outer galvanized steel tapping flange and inner frame are manufactured with pre-punched mounting holes. For a square fit, keep the door panel closed while installing. See installation instructions supplied with panel.

ORDERING:

- WHEN ORDERING, PLEASE SPECIFY WALL OR CEILING APPLICATION.
- PLEASE ORDER BY ROUGH OPENING SIZE.
- WHEN ORDERING THE SECOND DIMENSION GIVEN IS THE HINGE SIDE. (ie. 457mm x 610mm [18" x 24"], THE 610mm [24"] DIMENSION IS THE HINGE SIDE.
- **THESE DOORS ARE NON-RETURNABLE.**

OPTIONS: * - DENOTES ADDITIONAL COST.

- RAISED KNURLED KNOB.
- * - 1½" MORTISE PREP ONLY.
- * - 1½" MORTISE PREP COMPLETE WITH MORTISE CYLINDER.
- * - CONTINUOUS PIANO HINGE.
- * - 304 STAINLESS STEEL WITH A NO.4 POLISHED FINISH ON THE EXTERIOR SURFACE c/w CONTINUOUS PIANO HINGE.

WARRANTY:

One Year Limited warranty. For complete details see **Access Door** warranty document.

FCB-150 STANDARD SIZES
Single leaf construction for walls and ceilings.

Rough Opening Size W x H		No. of Latches/ Locks	Weight in kgs.	Weight in lbs.
Metric (mm)	Inches			
203 x 203	8 x 8	1	3.17	7.00
254 x 254	10 x 10	1	4.08	9.00
305 x 305	12 x 12	1	4.98	11.00
356 x 356	14 x 14	1	6.35	14.00
406 x 406	16 x 16	1	7.71	17.00
457 x 457	18 x 18	1	9.07	20.00
559 x 559	22 x 22	1	12.24	27.00
559 x 762	22 x 30	1	15.42	34.00
559 x 914	22 x 36	1	18.59	41.00
610 x 610	24 x 24	1	13.60	30.00
610 x 762	24 x 30	1	16.23	36.00
610 x 914	24 x 36	1	19.50	43.00

↑ ↑ Hinge Side

Net Opening = Width minus 77mm [3"]
 Height minus 39mm [1½"]



Model FCB-150 wall and ceiling fire-rated panels are manufactured under the factory inspection service of Intertek (Warnock Hersey) and have a label reading: "Listed access frame and insulated fire door assembly **2 hour fire rating. Vertical and Horizontal Installation.**" Temperature rise maximum 139°C / 250°F at 30 minutes, 250°C / 450°F at 60 minutes.

PROJECT SCHEDULE

- millimeters
- inches

Qty	Rough Opening Size		Options
	Width	Height	

↑ Hinge Side

PROJECT: _____

PURCHASE ORDER: _____

CONTRACTOR: _____

APPROVED BY: _____

ARCH. OR ENG.: _____

DATE: _____