


Ideal for high profile areas, which require long term durability and a pleasing appearance.


STANDARD CONSTRUCTION:

- MATERIAL** - SATIN FINISH GALVANIZED (GALVANNEALED) STEEL.
- PANEL** - 1.31mm [18 ga.], SELF CLOSING.
- LINER** - 0.85mm [22ga.]
- FRAME** - 1.61mm [16 ga.] UP TO AND INCLUDING 762mm x 1219mm [30" x 48"]. LARGER SIZES 1.99mm [14ga.]
- FLANGE** - RECESSED FLANGE 32mm [1¼"] WIDE, RECESSED 16mm [5⁄8"].
- HINGE** - CONTINUOUS ROD HINGE.
- LATCH** - ¼" ALLEN KEY, WITH INTERIOR RELEASE.
- INSULATION** - 38mm [1½"] HIGH TEMPERATURE.
- FINISH** - RUST INHIBITIVE PRIME COAT (OFF-WHITE).

* Specifications subject to change without notice.



FRONT ELEVATION



ROUGH OPENING IS EQUIVALENT TO DOOR SIZE ORDERED

SECTION A-A


PROJECT: _____

CONTRACTOR: _____

ARCH. OR ENG.: _____

DATE: _____

These drawings are the property of Maxam Metal Products Ltd. and incorporates information which is proprietary. Publication and/or public distribution in whole or in part is expressly prohibited without the prior written consent of Maxam Metal Products Ltd. The information herein remains the property of Maxam Metal Products Ltd. All rights reserved.

DWN BY KB	DATE Feb. / 2014	DWG. NO. Sheet 1 of 3	REV. 
--------------	---------------------	--------------------------	---

INSTALLATION:

The recessed outer concealed flange is manufactured with mounting holes.

For a square fit, keep the door panel closed while installing.

Install before your finishing material is applied. See installation instructions supplied with panel.

WARRANTY:

One Year Limited warranty. For complete details see **Access Door** warranty document.

ORDERING:

- WHEN ORDERING, PLEASE SPECIFY WALL OR CEILING APPLICATION.
- PLEASE ORDER BY ROUGH OPENING SIZE.
- WHEN ORDERING THE SECOND DIMENSION GIVEN IS THE HINGE SIDE. (ie. 457mm x 610mm [18" x 24"], THE 610mm [24"] DIMENSION IS THE HINGE SIDE.

- THESE DOORS ARE NON-RETURNABLE.

FCL-150 STANDARD SIZES
Single leaf construction for walls and ceilings.

Rough Opening Size W x H		No. of Latches/Locks	Weight in kgs.	Weight in lbs.
Metric (mm)	Inches			
203 x 203	8 x 8	1	3.17	7.00
254 x 254	10 x 10	1	4.08	9.00
305 x 305	12 x 12	1	4.98	11.00
406 x 406	16 x 16	1	7.71	17.00
457 x 457	18 x 18	1	9.07	20.00
559 x 559	22 x 22	1	12.24	27.00
559 x 762	22 x 30	1	15.42	34.00
559 x 914	22 x 36	1	18.59	41.00
610 x 610	24 x 24	1	13.60	30.00
610 x 914	24 x 36	1	19.50	43.00
762 x 762	30 x 30	1	19.50	43.00
762 x 1219	30 x 48	2	29.93	66.00
914 x 914	36 x 36	2	27.21	60.00

Single leaf construction for walls only.

914 x 1219	36 x 48	2	34.92	77.00
1219 x 1219	48 x 48	2	44.45	98.00
1219 x 1524	48 x 60	2	55.33	122.00



Net Opening = Width minus 83mm [3¼"]
 Height minus 39mm [1½"]



Model FCL-150 wall and ceiling fire-rated panels are manufactured under the factory inspection service of Intertek (Warnock Hersey) and have a label reading: "Listed access frame and insulated fire door assembly **2 hour fire rating. Vertical and Horizontal Installation.**" Temperature rise maximum 139°C / 250°F at 30 minutes, 250°C / 450°F at 60 minutes.

PROJECT SCHEDULE

- millimeters
 - inches

Qty	Rough Opening Size		Wall Application	Ceiling Application
	Width	Height		
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>



PROJECT: _____

CONTRACTOR: _____

ARCH. OR ENG.: _____

DATE: _____

PURCHASE ORDER: _____

APPROVED BY: _____

OPTIONS: * - DENOTES ADDITIONAL COST.


MATERIAL :-

- STANDARD MATERIAL - GALVANNEALED STEEL. SEE SHEET 1 OF 3.
- * - OPTIONAL MATERIAL - 304 STAINLESS STEEL WITH A NO. 4 POLISHED FINISH ON THE EXTERIOR SURFACE c/w CONTINUOUS PIANO HINGE.
- * - CONTINUOUS PIANO HINGE.
 NOTE: GREATER THAN 1219mm [48"] IN A WALL POSITION A CONTINUOUS PIANO HINGE IS STANDARD.


HARDWARE :-

- STANDARD HARDWARE - ¼" ALLEN KEY. SEE SHEET 1 OF 3.
- OPTIONAL HARDWARE - **NOTE: TWO LATCHES ARE REQUIRED ON DOORS LARGER THAN 762mm x 762mm [30" x 30"]. SEE SHEET 2 OF 3.**

ONE LATCH



TWO LATCHES


CENTER LATCH

- ALLEN KEY
- RAISED KNURLED KNOB.
- * - NON-LOCKING HANDLE.

TOP LATCH

- ALLEN KEY
- RAISED KNURLED KNOB.
- * - NON-LOCKING HANDLE.

BOTTOM LATCH

- ALLEN KEY
- RAISED KNURLED KNOB.
- * - NON-LOCKING HANDLE.

PROJECT: _____

PURCHASE ORDER: _____

CONTRACTOR: _____

APPROVED BY: _____

ARCH. OR ENG.: _____

DATE: _____