

**Model NGS – Gasketed, Interior / Exterior - Stainless Steel**

**Door:** 1.61mm (16ga) 304 stainless steel.

**Frame:** 1.61mm (16ga) 304 stainless steel with a 19mm (3/4”) or 32mm (1 ¼”) flange.

**Hinge:** Continuous stainless steel piano hinge (opens 180°).

**Gasket:** 3mm x 13mm (1/8” x ½”).

**Latch:** Screwdriver operated cylinder cam latch.

**Finish:** No. 4 polished stainless steel finish on the exterior surface.

**Performance Criteria:**

Model NGS met the performance criteria as per CSA A440-00 (windows) for an Air Infiltration of A-3 for both 75 Pa and 300 Pa, for Air Ex-infiltration the sample met an A-3 rating at 75 Pa and A-2 rating at 300 Pa. In Water Tightness by Static Pressure the door sample met a B-1 rating, subject to using an optional watertight mechanism.

Testing performed by Intertek (Warnock Hersey)

Van-Met Access Doors by:  
MAXAM METAL PRODUCTS LTD.  
Telephone: +1(604) 433-4243  
Fax: +1(604) 433-4148

Toll Free Telephone: 1-866-446-2926  
Toll Free Fax: 1-866-436-2926