

Model FFM, uninsulated for wall application

Rough Opening Size W x H Hinge Side		Stock Sizes	No. of Latches/Locks	Weight in Kgs.	Weight in Lbs.
Metric (mm)	Inches ↓				
152 x 152	6 x 6		1	1.36	3.00
203 x 203	8 x 8	•	1	2.04	4.50
203 x 305	8 x 12		1	2.50	5.50
254 x 254	10 x 10	•	1	2.60	5.75
305 x 305	12 x 12	•	1	3.06	6.75
305 x 406	12 x 16		1	4.13	9.10
305 x 457	12 x 18		1	4.53	10.00
305 x 610	12 x 24		1	5.89	13.00
356 x 356	14 x 14		1	4.08	9.00
356 x 508	14 x 20		1	5.89	13.00
406 x 406	16 x 16		1	5.21	11.50
406 x 508	16 x 20		1	6.01	13.25
406 x 610	16 x 24		1	7.82	17.25
457 x 457	18 x 18		1	6.12	13.50
457 x 610	18 x 24		1	8.73	19.25
508 x 508	20 x 20		1	8.05	17.75
508 x 610	20 x 24		1	9.07	20.00
508 x 762	20 x 30		1	11.00	24.25
559 x 559	22 x 22		1	9.18	20.25
559 x 762	22 x 30		1	11.79	26.00
610 x 610	24 x 24		1	10.43	23.00
610 x 762	24 x 30		1	12.47	27.50

Net Opening = Metal Stud Framing: **Width minus 6 mm (1/4")**
Height minus 6 mm (1/4")

Net Opening = Wood Stud Framing: **Width minus 38 mm (1 1/2")**
with 5/8" Drywall Lining Height minus 38 mm (1 1/2")

When ordering, the second dimension given (shown in red) is the hinge side.