

## **Model NWR – Weather Resistance**

**Door:** 1.31mm (18ga) satin finished galvanized steel.

**Liner:** 1.31mm(18ga) satin finished galvanized steel.

**Frame:** 1.31mm (18ga) satin finished galvanized steel  
with a 51mm (2”) exterior flange.

**Gasket:** 6mm x 25mm (1/4” x 1”).

**Hinge:** Continuous stainless steel piano hinge (opens 180°).

**Latch:** Locking handle, operable from handle side only.

**Finish:** Rust inhibitive off-white prime coat.

**Insulation:** 51mm (2”) rigid fiberglass.

### **Performance Criteria:**

Model NWR met the performance criteria as per CSA A440-00 (windows) for an Air Tightness rating of A-3 at infiltration pressure of 75 Pa and 300 Pa and at ex-filtration pressures of 75 Pa and 300 Pa. In Water Tightness by Static Pressure the door met a B-4 rating, subject to using an optional watertight mechanism.

Testing performed by Intertek (Warnock Hersey)

Van-Met Access Doors by:  
MAXAM METAL PRODUCTS LTD.  
Telephone: +1(604) 433-4243  
Fax: +1(604) 433-4148

Toll Free Telephone: 1-866-446-2926  
Toll Free Fax: 1-866-436-2926