MODEL RHS-4 (3'-0" x 4'-0"): Insulated Steel Curb Roof Hatch

Material:	**Cover:** 14 gauge satin finish galvannealed steel.
	Cover Liner: 22 gauge satin finished galvannealed steel.
	Curb Frame: 12" high in 14 gauge satin finish galvannealed steel.
Latch:	Zinc plated spring latch with inside and outside padlock hasps.
Lid/Cover Operator:	Heavy duty pintle/**spring** counter-balancing operators encased in a 12 gauge galvannealed steel **hinge** bracket assembly.
Hold Open Arm:	Powder coated safety red steel hold open arm with release handle.
Gasket:	Enhanced weather resistant EPDM.
Insulation:	1" thick polyisocyanurate insulation R-6 (5.6 LTTR) in cover. 1" thick polyisocyanurate insulation R-6 (5.6 LTTR) on curb.
Mounting Flange:	3 ½" wide complete with 7/16" mounting holes.
Finish:	Rust inhibitive grey primer.
Warranty:	Maxam Metal Products Ltd. guarantees all roof hatch products to be free from defects in workmanship for a time period of five years from the date of shipping.

MAXAM METAL PRODUCTS LTD.
Telephone: +1(604) 433-4243
Fax: +1(604) 433-4148

Toll Free Telephone: 1-866-446-2926
Toll Free Fax: 1-866-436-2926